



Ref. Certif. No

NO126005

## IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

## Product

LED Power Supply

## Name and address of the applicant

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.  
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong  
China

## Name and address of the manufacturer

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.  
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong  
China

## Name and address of the factory

See next page(s)

Note: When more than one factory, please report on page 2

 Additional Information on Page 2

## Ratings and Principal characteristics

PRI: Max. 0.4 A, 220-240 V~, 50/60 Hz,  
More rating, see additional information.  
Independent type, Class II; SELV, constant current output, thermal protected 110 °C, ta: 45 °C,  
tc: 80 °C / 85 °C

## Trademark /Brand (If any)



## Customer's Testing Facility (CTF) Stage used

## Model/Type Ref

FLS-15-350 0-10 LA, FLS-25-600 0-10 LA, FLS-44-1050 0-10 LA, FLS-60-1700 0-10 LA,  
FLS-60-1700 LA EXC, FLS-60-1500 LA EXC, FLS-60-1500 LD ECO, LS-40-xxxx LI ECO

## Additional information (If necessary may also be reported on Page 2)

 Additional Information on Page 2

## A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017  
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

## As shown in the Test Report Ref. No. which forms part of this Certificate

REP007638

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway  
Date: 15-03-2023

Jiyea Gim

Signature: Jiyea Gim  
Certification department



Ref. Certif. No

NO126005

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.  
No.4, East Huanzhen Road, Beijiao Shunde, Foshan, Guangdong  
China

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD  
West Zone, Ji An County Industrial Park, Ji an County  
Jiangxi Province  
China

### Additional Information (if necessary)

SEC:

FLS-15-350 0-10 LA: Max. 14.7 W, 0.12-0.35 A, 9-42 Vd.c. (under load), max. 59 Vd.c. (no-load)

FLS-25-600 0-10 LA: Max. 25.2 W, 0.2-0.6 A, 9-42 Vd.c. (under load), max. 59 Vd.c. (no-load)

FLS-44-1050 0-10 LA: Max. 44.1 W, 0.65-1.05 A, 9-42 Vd.c. (under load), max. 59 Vd.c. (no-load)

FLS-60-1700 0-10 LA: Max. 61.2 W, 1.10-1.70 A, 12-42 Vd.c. (under load), max. 59 Vd.c. (no-load)

FLS-60-1700 LA EXC: Max. 61.2 W, 1.10-1.70 A, 24-42 Vd.c. (under load), max. 55 Vd.c. (no-load)

FLS-60-1500 LD ECO and FLS-60-1500 LA EXC: Max. 63.0 W, 1.15-1.50 A, 24-42 Vd.c. (under load), max. 55 Vd.c. (no-load)

LS-40-xxxx LI EC0: Max. 40.4 W, 0.60-1.05 A, 24-42 Vd.c. (under load), max. 52 Vd.c. (no-load)

The 'xxxx' is for the output current and represents the number from 600 mA to 1050 mA in step of 50 mA, for example, 1050 means the output current is 1050 mA.



Philip Pedersen vei 11,  
NO-1366 Lysaker, Norway

Date: 15-03-2023

*Jiyea Gim*

Signature: Jiyea Gim  
Certification department