



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2023011002567542

NAME AND ADDRESS OF THE APPLICANT

Eaglerise Electric & Electronic (China) Co., Ltd.
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong
Province, P.R.China

NAME AND ADDRESS OF THE MANUFACTURER

Eaglerise Electric & Electronic (China) Co., Ltd.
No.A3, Guicheng Sci-Tech Industrial Park, Jianping Road, Nanhai District, Foshan City, Guangdong
Province, P.R.China

NAME AND LOCATION OF THE FACTORY

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

PRODUCT NAME,MODEL AND SPECIFICATION

A.C. Supplied Electronic Controlgear For LED Modules (Independent, Constant Voltage Mode, SELV,
IP20, Class II, Non-dimmable, ta: 45 °C, tc:75/80/90°C, Suitable For Direct Mounting On Normally
Flammable Material, Temperature Declared Thermally Protected: 110°C)
See Appendix; 220-240V~ 50/60Hz.

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

Valid from: Jan.19,2024

Valid until: May.03,2028

Date of original issued: Aug.29,2023

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2023011002567542

Appendix: Page 1 of 1

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

型号	输出参数			ta(°C)	tc(°C)
	输出电流 (Max.A)	恒定输出 电压(Vdc)	输出功率 Max.(W)		
LS-30-12 LI EXC	2.5	12	30	45	75
LS-30-24 LI EXC	1.25	24	30	45	75
LS-60-12 LI EXC	5.0	12	60	45	90
LS-60-24 LI EXC	2.5	24	60	45	90
LS-75-12 LI EXC	6.25	12	75	45	90
LS-75-24 LI EXC	3.13	24	75	45	90
LS-30-12 LI1 EXC	2.5	12	30	45	80
LS-30-24 LI1 EXC	1.25	24	30	45	80
LS-60-12 LI1 EXC	5.0	12	60	45	90
LS-60-24 LI1 EXC	2.5	24	60	45	90
LS-75-12 LI1 EXC	6.25	12	75	45	90
LS-75-24 LI1 EXC	3.13	24	75	45	90
LS-75-48 LI EXC	1.56	48	75	45	90

输入: 220-240V~ 50/60Hz

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE