

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OC

Product
ProduitName and address of the applicant
Nom et adresse du demandeurName and address of the manufacturer
Nom et adresse du fabricantName and address of the factory
Nom et adresse de l'usineNote: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la deuxième pageRatings and principal characteristics
Valeurs nominales et caractéristiques principalesTrademark (if any)
Marque de fabrique (si elle existe)Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeurModel / Type Ref.
Ref. De typeAdditional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la deuxième page)A sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à laAs shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport de tests numéro de référence qui constitue partie de ce CertificatThis CB Test Certificate is issued by the National Certification Body
Ce Certificat de test OC est établi par l'Organisme National de Certification

LED Power Supply

Foshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde
Foshan Guangdong
ChinaFoshan Eaglerise Power Science & Technology (Shunde) Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde
Foshan Guangdong
China☒ Additional information on page 2

PRI: max. 0.12 A, 220-240 V~, 50/60 Hz, PF>0.8 SEC: Max. 12.6 W, 200-700 mA, 7-48 Vdc (under load), max. 60 Vdc (no-load).



SS-9-XXX MB-G, SS-12-XXX MB-G

Built-in LED power supply with double or reinforced insulation, providing SELV output, constant current output, thermally protected 110°C, IP44 only for LED driver body. ta: 50 °C, tc: 75 °C (For SS-9-XXX MB-G) ta: 50 °C, tc: 80 °C (For SS-12-XXX MB-G) The 'XXX' is for the output current and represents the number from 200 to 700 increasing in step of 50, for example, 700 means the output current is 700 mA.

☐ Additional information on page 2IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

462282

Philip Pedersens vei 11,
NO-1366 Lysaker, Norway

Date: 30-03-2022

Jiyea Gim

Signature: Jiyea Gim
Certification Department



Ref. Certif. No.

NO121894

Foshan Eaglerise Power Science & Technology (Shunde)
Co., Ltd.
No.4, East Huanzhen Road, Beijiao Shunde
Foshan Guangdong
China

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO.,
LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China



Philip Pedersens vei 11,
NO-1366 Lysaker, Norway

Date: 30-03-2022

Jiyea Gim

Signature: Jiyea Gim
Certification Department