



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2024011002656628

NAME AND ADDRESS OF THE APPLICANT

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

NAME AND ADDRESS OF THE MANUFACTURER

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

NAME AND LOCATION OF THE FACTORY

Eaglerise Electric & Electronic (Ji An) Co., Ltd.
Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An
County, Jiangxi Province, P.R.China

PRODUCT NAME,MODEL AND SPECIFICATION

A.C. Supplied Electronic Control Gear For LED Modules (Independent, Constant Current Mode,
Controlled Port Dimming, SELV, ta:45°C, tc:75/85°C, Suitable For Normally Flammable Material
Surfaces, Temperature Declared Thermally Protected: 110°C)
See Appendix; Input : 220-240V~ 50/60Hz.

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

Valid from: Jul.12,2024

Valid until: Jul.11,2029

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2024011002656628

Appendix: Page 1 of 1

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

型号	输出				ta (°C)	tc (°C)	备注
	恒定电 流 (mA)	电压 (Vdc)	最大空载 电压 (Max.Vdc)	功率 (Max.W)			
FLS-20-500 DALI-2 LD PRO	80	2.5-49	60	3.9	45	75	DALI 调光 可通过拨 码档位调 节输出电 流
	100			4.9			
	120			5.9			
	150			7.4			
	180			8.8			
	200			9.8			
	220			10.8			
	250			12.3			
	280			13.7			
	300			14.7			
	350			17.2			
	400			19.6			
	450	2.5-44.5		20.0			
	500	2.5-40		20.0			
FLS-20-500 DALI-2 LN PRO	80-400	2.5-49	60	3.92-19.6	45	75	DALI 调光
	401-450	2.5-44.5		17.85-20			
	451-500	2.5-40		18-20			
FLS-30-700 DALI-2 LN PRO	150-200	2.5-49	60	7.35-9.8	45	85	通过 NFC 调节输出 电流
	250-350	2.5-49		12.25-17.2			
	400-650	2.5-45		18-29.3			
	700	2.5-42		29.4			

输入：220-240V~ 50/60Hz 0.2A

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.