

CERTIFICATE

Issued to:
Applicant:
**EAGLERISE ELECTRIC & ELECTRONIC (JI AN)
CO., LTD**
West Zone, Ji An County Industrial Park, Ji An
County
343100 Ji An City, Jiangxi, China

Licensee:
**Foshan Eaglerise Power Science & Technology
(Shunde) Co.,Ltd.**
No.4, East Huanzhen Road, Beijiao Shunde
528000 Foshan, Guangdong, China

Product : LED power supply
Trade name(s) : ASTRAPOWER or EAGLERISE
Type(s)/model(s) : LS-150-24 DALI-2 LI1, LS-45-24 DALI-2 LI1, LS-75-48 LI EXC and
LS-80-24 DALI-2 LI1

The product and any acceptable variation thereof as specified in the Annex to this certificate and the documents referred to therein.

DEKRA hereby declares that the above-mentioned product has been certified based on:

- a type test according to EN 61347-1:2015, EN 61347-1:2015/A1:2021, EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017 and EN IEC 62384:2020
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 2178893


DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 29 August 2024 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 35-146055

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



K. Lin
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

Product	: LED power supply
Trade name(s)	: ASTRAPOWER or EAGLERISE
Type(s)/model(s)	: LS-150-24 DALI-2 LI1, LS-45-24 DALI-2 LI1, LS-75-48 LI EXC and LS-80-24 DALI-2 LI1
Class	: Class II
Degree of protection	: IP20
Ambient temperature (ta)	: 45 °C
Additional information	: SELV, independent, non-inherently short circuit proof, 110 °C thermal protection

Product data – type LS-150-24 DALI-2 LI1, LS-45-24 DALI-2 LI1 and LS-80-24 DALI-2 LI1

Rated voltage	: 220-240 Vac/dc
Rated frequency	: 0/50/60 Hz
Power factor	: >0,95
Max. case temperature (tc)	: 85°C

Product data – type LS-75-48 LI EXC

Rated voltage	: 220-240 Vac
Rated frequency	: 50/60 Hz
Power factor	: 0,1-0,95
Max. case temperature (tc)	: 90°C

TESTS**Test requirements**

EN 61347-1:2015
EN 61347-1:2015/A1:2021
EN 61347-2-13:2014
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

Test result

The test results are documented in DEKRA test file 492014500.

Additional information


The list of components is laid down in test report 4920145.50,4920145.51.


Conclusion

The examination has confirmed that all requirements were met.

Factory location

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji An County
343100 Ji An City, Jiangxi, China

Trade name : EAGLERISE stands for EAGLERISE

ASTRAPOWER stands for ASTRAPOWER