


8W Bluetooth Dimming power supply



■ Approve



Features

- For luminaires of protection Class II, SELV, independent
- Input Voltage: 220-240VAC
- Protections: OLP/OVP/OTP
- Power Factor: > 0.5
- Efficiency: 80%
- 5 years warranty
- IP20

Applications


- LED down light, LED spot light

◆ Description

LS-8-XXX Blue SI-MJ is a 8W constant current LED driver that operates from 198-264Vac input with 100-235mA output current and a forward voltage range from 30 to 40Vdc. With it's compact dimensions from 115 x 30 x 20.5 mm it is easy to integrate in LED down light. To ensure trouble-free operation, protection is provided against over Load.

◆ Model code

LS-8-XXX Blue SI-MJ



◆ Specification

Output	Constant Current (mA)	100mA	120mA	160mA	180mA	200mA	235mA
	Voltage Range(VDC)	30-40VDC					
	Unload voltage Max.(VDC)	59VDC					
	Current Accuracy	±7%					±5%
	Output HF current ripple(≥1KHz)	≤±5%					
	Output LF current ripple(≤120Hz)	≤±3%					
	SVM	≤0.4					
	Pst	≤1					
	Efficiency(Typ.)	75%@230VAC, full load			80%@230VAC, full load		
Input	Rated input voltage(VAC)	220-240VAC					
	Range of input voltage(VAC)	198-264VAC					
	Maximum voltage	300VAC@1 h maximum,unit might not operate in this abnormal condition					
	Frequency(Hz)	50/60 Hz					
	Displacement factor	≥0.5@220-240VAC, full load					
	Power Factor	≥0.5@220-240VAC, full load					
	Input Current max	0.06A	0.07A	0.08A	0.09A	0.1A	0.11A
	Start-up time	< 0.8S					
	No Load Power	≤0.5W					
	Standby Power	≤0.5W					
	Network standby power	≤0.5W					
Dimming	Dimming	YES					
	Dimming mode	Bluetooth					
	Dimming depth	5%					
	Dimming current range	5~100%					
Protection	Over Load Protection	103-130%					
		YES/Auto Resume					
	Over Voltage Protection	>45VDC					
		YES/Auto Resume					
capability	Surge capability (L-N)	1KV					
	Surge capability (L/N-Ground)	NA					
Environment	Operating Temperature	-20°C...+45°C					
	Humidity	20%-90%RH					
	Tc	75°C					
	Storage Temperature	-20°C...+80°C					
	Life time	> 50,000h@Tc=75°C,230VAC					
	Noise	≤25dB(A)@20cm					
Surface	Dimension	115X30X20.5(LXWXH)mm					
Standards	Safety	GB19510. 1, GB19510. 14,EN61347- 1, EN61347-2- 13					

	EMC	GB/T17743, GB17625. 1,EN55015, EN61000-3-2, EN61000-3-3, EN61547,EN55015, EN61000-3-2, EN61000-3-3, EN61547
	Energy Efficiency	Erp2.0 EU 2019/2020
	RoHS	RoHS (2011/65/EU) (EU)2015/863
Note	1.All parameters NOT specially mentioned are measured at 230VAC input , full load and 25°C of ambient temperature. 2.Ripple & Noise are measured at 20MHz of bandwidth by using a 300mm twisted pair-wire terminated with a 0.1uF & 47 uF parallel capacitor. 3.The over-temperature protection of the product is provided by the IC. 4.All Eaglerise power supply are complied with EMI regulations. Since they are belong to component and will be installed inside system enclosure. When they are integrated into a system, the EMI characteristics of the system must be re-verified again.	


◆ Model list

Number	Model number	Output			
		Current (mA)	Voltage (VDC)	Voltage No load (VDC)	Power (W)
1	*LS-8-100 Blue SI-MJ	100	30-40	59	4
2	*LS-8-120 Blue SI-MJ	120			4.8
3	*LS-8-160 Blue SI-MJ	160			6.4
4	*LS-8-180 Blue SI-MJ	180			7.2
5	*LS-8-200 Blue SI-MJ	200			8
6	*LS-8-235 Blue SI-MJ	235			9.4

*Regular stockpile products

◆ Inrush Current


I_{peak}	Twidth	B10	B16	B20	C10	C16	C20
11.5A	100μs	72pcs	116pcs	145pcs	72pcs	116pcs	145pcs




Remarks:

- 1.The number of drives mounted under different MCBs in the table is the maximum value. Please do not exceed this number during installation.
- 2.Different brands and models of miniature circuit breakers, the number of drives mounted will be slightly different.

◆ Wiring diagram



◆ 2D diagram



◆ Wiring & Connections

Specification item		Value (Unit)
Input	Input wire cross-section	0.5...1.5 mm ²
	Input wire gauge.	16...20 AWG
	Input wire strip length	7...9mm
Output	Output wire cross-section	0.5...1.5 mm ²
	Output wire gauge.	16...20 AWG
	Output wire strip length	7...9mm

◆ Recommended wire

Wire cross-section	Wire type
2*0.5mm ²	H03VVH2-F 2core
2*0.75mm ²	H03VVH2-F 2core
1.5mm ²	CCC 08(RV-90)
16AWG(1.25mm ²)	UL1015


Note: Solid wire is risky to use on an angled terminal. Stranded wire is recommended for this kind of use.

◆ Packaging


Model	Product Dimensions(mm)	weight/piece	Outer carton dimension(mm)	Quantity/carton	Net weight/carton(Kg)	Gross weight/carton(Kg)
LS-8-XXX Blue SI-MJ	115X30X20.5mm	45.2	385X285X225mm	203	9.176	16.65

◆ Curve for LS-8-XXX Blue SI-MJ, $I_o=235mA$


Lifetime vs. Temperature Curve




Efficiency vs. Load




Power Factor Characteristics



THD vs. Load



◆ Operating window



◆ Revision Updates

ITEM	BEFORE	AFTER	VERSION	DATE
Initial			A	2025/02/11

Remark:The final interpretation of the contents of the specification belongs to Eaglerise Electric & Electronic (China) Co., Ltd.

Tel: +86-0757-86256822, +86-0757-86256831

E-mail: sales@eaglerise.com

Website : <https://lighting.eaglerise.com>



EAGLERISE



Manual