

CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC25010484016 Valid from: Aug.27,2025 Valid until:Aug.26,2030

NAME AND REGISTERED Eaglerise Electric & Electronic (Ji An) Co., Ltd.

ADDRESS OF THE APPLICANT Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An

County, Jiangxi Province, P.R.China

Eaglerise Electric & Electronic (Ji An) Co., Ltd. NAME AND REGISTERED

ADDRESS OF THE Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An

MANUFACTURER County, Jiangxi Province, P.R.China

NAME AND LOCATION Eaglerise Electric & Electronic (Ji An) Co., Ltd.

OF THE FACTORY Southwest Corner, Crossing Between Panlong Road And Chaoyang Road, Industrial Park, Ji An

County, Jiangxi Province, P.R.China

PRODUCT NAME, MODEL Electrical Supply Track System For Luminaires (Adaptor , Built-in A.C. Supplied Electronic AND SPECIFICATION

Controlgear for LED Modules, SELV, Class II, IP20, Suitable For Direct Mounting On Normally

Flammable Material Surfaces, ta:35°C, tc:75°C/80°C, Temperature Declared Thermally

Protected:110°C)

See Appendix. 220-240V ~ 50/60Hz

THE STANDARDS AND IEC 60570: 2019;GB/T 7000.1-2023 **TECHNICAL REQUIREMENTS**

FOR THE PRODUCTS

TYPE OF CERTIFICATION

SCHEMES

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC12-465431-2024.

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Type Testing of Product + Follow up Factory Inspection

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn











CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC25010484016

page1of1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

型号	输出电压 (VDC)	最大输出电流(A)	最大输出功率(W)	调光方式
FDS-42-1050 DALI-2 LD EXC		0.3A	12.6	
		0.35A	14.7	
		0.4A	16.8	
		0.45A	18.9	
		0.5A	21	
	10-42VDC	0.55A	23.1	
		0.6A	25.2	
		0.65A	27.3	Dali
		0.7A	29.4	Dall
		0.75A	31.5	ALLE TO THE REAL PROPERTY.
		0.8A	33.6	The same of the sa
	10-40VDC	0.85A	34	
		0.9A	36	
		0.95A	38	
		1.00A	40	
		1.05A	42	
FDS-42-1050 LD EXC S		0.7A	28	
	A SHELLER	0.75A	30	
	30-40VDC	0.8A	32	
		0.85A	34	
		0.9A	36	
		0.95A	38	不可调光
		1.00A	40	
		1.05A	42	
FDS-42-1050 CCT LD	10-42VDC	0.8A	33.6	
		0.9A	36.0	
	10-40VDC	1.05A	42.0	

Uout=59Vdc;输入:220-240V~ 50/60Hz

