



Ref. Certif. No

NO135884

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

LED Power Supply

Name and address of the applicant

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China

Name and address of the manufacturer

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China

Name and address of the factory

EAGLERISE ELECTRIC & ELECTRONIC (JI AN) CO., LTD
West Zone, Ji An County Industrial Park, Ji an County
Jiangxi Province
China

Note: When more than one factory, please report on page 2

☐ Additional Information on Page 2

Ratings and Principal characteristics

PRI: max. 1.3 A, 220-240 V~, 0/50/60 Hz, PF 0.95, Centralized emergency power supply:
220-240 V dc; SEC: 30-200 W, max. 8.33 A, 12 Vdc / 24 Vdc / 48 Vdc, EOFI: 100%. Class II
EAGLERISE

Trademark /Brand (If any)



Customer's Testing Facility (CTF) Stage used

Model/Type Ref

US-xxx-yy LI EXC

Additional information (If necessary may also be reported on Page 2)

☒ Additional Information on Page 2

A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015, IEC 61347-1:2015/AMD1:2017
IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

As shown in the Test Report Ref. No. which forms part of this Certificate

REP111468

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 29-08-2025

Sweet Yuan

Signature: Sweet Yuan
Certification department



Ref. Certif. No

NO135884

Additional Information (if necessary)

Independent type, SELV, constant voltage output, thermal protected 110 °C, ta: 45 °C / 50 °C, tc: 85 °C / 90 °C, MM marking.

The 'xxx' in the type designation can be 30, 60, 100, 150 or 200, indicating approximate output power in watt.

The 'yy' can be 12, 24 or 48, indicating the output voltage in volt. for example, 12 means the output voltage is 12 Vdc, 48 means the output voltage is 48 Vdc.



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 29-08-2025

Signature: Sweet Yuan
Certification department