

ATTESTATION OF CONFORMITY

Issued to: EAGLERISE ELECTRIC & ELECTRONIC (JIAN) CO., LTD
West Zone, Ji an County Industrial Park, Ji an County, Jiangxi Province, China

For the product: LED power supply

Trade name:



Type/Model: See annex

Ratings: 100-277 Vac, 50/60Hz

Manufactured by: EAGLERISE ELECTRIC & ELECTRONIC (JIAN) CO., LTD
West Zone, Ji an County Industrial Park, Ji an County, Jiangxi Province, China

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN IEC 55015:2019 + A11:2020
EN IEC 61547:2023
EN IEC 61000-3-2:2019 + A1:2021 + A2:2024
EN 61000-3-3:2013 + A1:2019 + A2:2021 + AC:2022-01

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no 4951219.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic Compatibility Directive (EMC) 2014/30/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 20 May 2026

Number: 4951219.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,
Guangzhou Branch

Clover Chen

Clover Chen
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Annex

Document no. : 4951219.01AOC

Type/Model:

Model	Input				Output				Remark
	Voltage (VAC)	Max. Current(A)	Max. Power(W)	Frequency (Hz)	Constant current (mA)	Normal working voltage (Vdc)	No load working voltage (Vdc)	Max. Power(W)	
LX-8-70 LI EXC	100-277	0.065	5.34	50/60	70	27-42	59	2.9	Used the same PCB
LX-8-100 LI EXC		0.09	6.82		100			4.2	
LX-8-120 LI EXC		0.1	7.71		120			5	
LX-8-150 LI EXC		0.125	9.64		150			6.3	
LX-8-160 LI EXC		0.135	10.29		160			6.7	
LX-8-180 LI EXC		0.15	11.25		180			7.6	
LX-8-200 LI EXC		0.15	11.43		200	27-40		8	
LX-8-220 LI EXC		0.15	12.56		220			8.8	
LX-12-250 LI EXC	100-277	0.175	14.42	50/60	250	27-42	59	10.5	Used the same PCB
LX-		0.195	16.14		280			11.8	

12-280 LI EXC									
LX-12-300 LI EXC		0.2	16.47		300	27-40		12	
LX-21-350 LI EXC	100-277	0.22	18.96	50/60	350	27-42	59	14.7	Used the same PCB
LX-21-400 LI EXC		0.25	21.67		400			16.8	
LX-21-450 LI EXC		0.285	24.39		450			18.9	
LX-21-500 LI EXC		0.32	27.10		500			21	
LX-21-550 LI EXC		0.32	27.33		550	27-38.5		21	
LX-40-600 LI EXC	100-277	0.57	32.13	50/60	600	24-42	59	25.2	Used the same PCB
LX-40-650 LI EXC			34.81		650			27.3	
LX-40-700 LI EXC			37.49		700			29.4	

LX-40-750 LI EXC			40.17		750		31.5	
LX-40-800 LI EXC			42.85		800		33.6	
LX-40-850 LI EXC			45.51		850		35.7	
LX-40-900 LI EXC			48.19		900		37.8	
LX-40-950 LI EXC			50.87		950		39.9	
LX-40-1000 LI EXC			53.55		1000	24-40	40	
LX-40-1050 LI EXC			51.55		1050	24-38.5	40.4	

End